

Listing of: (memory data)

Channel Group: Measured Torque and Power Page 1 of 1

Printed on Jul 3, 2015 at 10:53:59

Test Description: Accel. Test - 600 rpm/second

EngSpd RPM	EngTrq lb-ft	EngPwr Hp	Boost psig	Fuel B lb/hr	A/F Ratio	Air 1 scfm	BSFC lb/hph	VolEff %
3300	694.0	436.1	0.0	0.0	0.00	0	0.000	0.0
3400	688.6	445.8	0.0	0.0	0.00	0	0.000	0.0
3500	683.2	455.3	0.0	0.0	0.00	0	0.000	0.0
3600	679.4	465.7	0.0	0.0	0.00	0	0.000	0.0
3700	684.2	482.0	0.0	0.0	0.00	0	0.000	0.0
3800	678.4	490.8	0.0	0.0	0.00	0	0.000	0.0
3900	676.0	502.0	0.0	0.0	0.00	0	0.000	0.0
4000	690.2	525.7	0.0	0.0	0.00	0	0.000	0.0
4100	692.6	540.7	0.0	0.0	0.00	0	0.000	0.0
4200	<u>700.8</u>	560.4	0.0	0.0	0.00	0	0.000	0.0
4300	697.0	570.6	0.0	0.0	0.00	0	0.000	0.0
4400	691.6	579.4	0.0	0.0	0.00	0	0.000	0.0
4500	691.6	592.6	0.0	0.0	0.00	0	0.000	0.0
4600	698.0	611.3	0.0	0.0	0.00	0	0.000	0.0
4700	698.0	624.6	0.0	0.0	0.00	0	0.000	0.0
4800	692.6	633.0	0.0	0.0	0.00	0	0.000	0.0
4900	683.8	638.0	0.0	0.0	0.00	0	0.000	0.0
5000	679.8	647.2	0.0	0.0	0.00	0	0.000	0.0
5100	667.6	648.3	0.0	0.0	0.00	0	0.000	0.0
5200	656.0	649.5	0.0	0.0	0.00	0	0.000	0.0
5300	647.2	653.1	0.0	0.0	0.00	0	0.000	0.0
5400	636.0	653.9	0.0	0.0	0.00	0	0.000	0.0
5500	626.6	<u>656.2</u>	0.0	0.0	0.00	0	0.000	0.0
5600	604.2	<u>644.2</u>	0.0	0.0	0.00	0	0.000	0.0
5700	573.8	622.7	0.0	0.0	0.00	0	0.000	0.0
5800	554.4	612.2	0.0	0.0	0.00	0	0.000	0.0
5900	545.0	612.2	0.0	0.0	0.00	0	0.000	0.0
6000	532.8	608.7	0.0	0.0	0.00	0	0.000	0.0
6100	498.6	579.1	0.0	0.0	0.00	0	0.000	0.0

Tändning 34-35 grader

SuperFlow WinDyn Software

Bestyckning

82 94
71 ↓ 71
80 92